Sharecall: 086 111 3968



### 6 Seater AC Shuttle

#### Introduction:

This unit easily handles 6 people either as a hotel shuttle, or transport around the estate or resort, making it one of the most cost effective and versatile transports in the traditionally golf styled range. This cart features the 48 Volt Curtis 1236 AC controller, Trojan T105 batteries, 5kW AC motor and can be optionally supplied with Battery Watering System or Li-lon maintenance-free batteries.



Model: Melex 48V 6 Seater AC Shuttle	
Battery	8 X Trojan T105 6V
Motor	5KW AC
Controller	Curtis 1236
General Specifications:	
Passenger capacity	6
Range based on flat road at a speed of 20km/h (km)	60Km +
Max. speed (km/h)	40
Minimum turning radius (m)	4.5
Max. climbing ability (loaded)	20%
Max. movement after brake	≤4m
Overall dimensions	3710x1200x1850mm
Max. loading weight	475kgs
Net weight	710kgs

## Melex Electrovehicles



# Technical Specification sheet

	Configurations: "S" stands for Standard configuration and "O" stands for Optional configuration	
PART DESCRIPTIONS	REMARKS	
Body	Steel framework + plastic front body + fiberglass rear body	S
Roof	injected plastic	S
Windshield	one-piece Organic glass	S
Windshield, hinged	\	S
Large Seats:		
1) backrest and cushion	Rebond seat + artificial leather	S
2) armrest	Formed	S
3) plastic seat bottom	\	S
Floor	rubber	S
Center storage basket	Large volume	S
Golf bag holder	1	S
Dashboard in black plastic finish	forward/reverse switch, battery capacity indicator, ignition key	S
Beverage holders	4 cups drink holders	S
Lighting system and horn	2 headlights, 2 front turn signals, 2 taillights( each combined 1 brake light with 1 turn signal), with DC-DC converter (converting from 48V to 12V), horn.	S
Glove box	\	S
Side trim	stainless steel	S
Score card holder	on steering wheel	S
Towing bracket	on front of golf car	S
Battery tray	to protect the battery liquid touching the frame	S
Motor	5Kw std, 4Kw optional	0
Battery	see above	+~
Controller	see above	+
Steering system	Single-stage rack and pinion steering system, automatic rocker compensating function	S
Brake system	4-wheel hydraulic brake and regenerative	S
Accelerator	Stepless speed change	S
Suspension system	Front and rear plate spring + cylinder hydraulic shock absorber	S
Driving mode	Rear axle two stage deceleration, motor direct driving	S
Rear axle	Gear ratio12.49:1	S
Tyre	205*50-10 4PR (together with 10*7 Steel wheel)	S
Reversing alarm	\	S
Wheel cap for 10" wheel	\	S

#### **ACCESSORIES:**

Charger	240V~50Hz-60Hz, output 48V, 25A High Frequency	S
On board charger	On-Board Mount	S

Sharecall: 086 111 3968