

2+2 Road Legal Golf Cart

NRCS and SA Transport approved 2+2 Seat Golf vehicle, featuring a 5kW AC drive and all additional safety features allowing road legal use, ideally suited to Golf and Lifestyle estates, campuses, small towns and coastal holiday towns.







Model: Melex 2+2 Seater Golf Road Legal SWB	
Battery	8 X Trojan T105 6V
Motor	5KW AC
Controller	Curtis 1236
Passenger capacity	2 + 2
Range based on flat road at a speed of 20km/h (km)	50 Km +-
Max. speed (km/h)	40
Minimum turning radius (m)	3.5
Max. climbing ability (loaded)	20%
Max. movement after brake	≤4m
Overall dimensions	2960x1200x1850mm
Max. loading weight	300kgs
Net weight	620kgs
Min Ground Clearance	120mm
Wheel Base	1700mm
Optional Solar Panel Roof Mounted and controller	220W

Melex Electrovehicles



Technical Specification sheet

	Configurations: "S" stands for Standard configuration and "O" stands for Optional configuration	
PART DESCRIPTIONS	REMARKS	
Body	Steel framework + plastic front body	S
Roof	Fibreglass	S
Windshield	one-piece Laminated glass	S
Wiper and Water Reservoir	1 L reservoir	S
Large Seats:	12100011011	
1) backrest and cushion	Rebond seat + artificial leather	S
2) armrest	Formed	S
3) seat belts	4 x inertia reel	s
Floor Cover	rubber	s
Uprights/Roll Cage	Carbon Steel, powder coating	S
Dashboard in black plastic finish	forward/reverse switch, battery capacity indicator, ignition key	S
Beverage holders	4 cups drink holders	S
Lighting system and horn	2 headlights, 2 front turn signals, 2 taillights(each combined 1 brake light with 1 turn signal), with DC-DC converter (converting from 48V to 12V), horn.	s
Dashboard and Meters	speed, mileage, headlight indicator, emergency light indicator, turn signal indicator, reverse indicator, forward/reverse switch, battery capacity indicator, ignition key (steering column)	S
Side trim	Aluminium	S
Score Card holder	on steering wheel	S
Towing bracket	on front of cart	S
Battery tray	to protect the battery liquid touching the frame	S
Rear axle	Gear ratio12.49:1	S
		0
Battery Watering System	Float caps, tubes, filling coupling	0
Steering system	RHD single-stage rack and pinion steering system, automatic rocker compensating function	s
Occurring system	4-wheel hydraulic drum brake + hand brake	- 3
Brake system	,	S
Accelerator	Stepless speed change	S
Suspension system	Front and rear plate spring + cylinder hydraulic shock absorber	S
Driving mode	Rear axle two stage deceleration, motor direct driving	S
Tyre	10x6 Aluminium rim, 205/50-10 tyres 4Ply	S
Reversing alarm	\	S

ACCESSORIES:

Charger	240V~50Hz-60Hz, output 48V, 25A High Frequency	S
	On-Board Mount option	0